

ITR8307



Features

- Thin
- Fast response time
- High sensitivity
- Pb free
- High analytic
- Compact
- The product itself will remain within RoHS compliant version
- Compliance with EU REACH
- Compliance Halogen Free(Br < 900ppm, Cl < 900ppm, Br+Cl < 1500ppm)

Description

The **ITR8307** consist of an infrared emitting diode and an NPN silicon phototransistor, encased side-by-side on converging optical axis in a black thermoplastic housing. The phototransistor receives radiation from the IR only. This is the normal situation. But when an object is in between, phototransistor could not receive the radiation.

Applications

- Various microcomputer control equipment
- Floppy disk driver
- Cassette type recorder
- Camera
- VCR

Device Selection Guide

| Device No. | Chip Material | LENS COLOR |
|------------|---------------|-------------|
| IR | GaAs | Water Clear |
| PT | Silicon | Water Clear |

Absolute Maximum Ratings (Ta=25°C)

| Parameter | | Symbol | Ratings | Unit |
|--|---|--------------------|---------|------|
| Input | Power Dissipation at(or below) 25°C Free Air Temperature | Pd | 75 | mW |
| | Reverse Voltage | V _R | 5 | V |
| | Forward Current | I _F | 50 | mA |
| | Peak Forward Current (*1) Pulse width ≤100μ s, Duty cycle=1% | I _{FP} | 1 | A |
| Output | Collector Power Dissipation | P _C | 75 | mW |
| | Collector Current | I _C | 50 | mA |
| | Collector-Emitter Voltage | B V _{CEO} | 30 | V |
| | Emitter-Collector Voltage | B V _{ECO} | 5 | V |
| Operating Temperature | | Topr | -25~+85 | °C |
| Storage Temperature | | Tstg | -30~+90 | °C |
| Lead Soldering Temperature (*2) (1/16 inch form body for 5 seconds) | | Tsol | 260 | °C |



(*1) tw=100 μ sec. , T=10 msec. (*2) t=5 Sec


Electro-Optical Characteristics (Ta=25°C)

| Parameter | | Symbol | Min. | Typ. | Max. | Unit | Conditions |
|--------------------------|------------------------|-----------------|------|------|------|-----------------|--|
| Input | Forward Voltage | V_F | --- | 1.2 | 1.6 | V | $I_F=20\text{mA}$ |
| | Reverse Current | I_R | --- | --- | 10 | μA | $V_R=5\text{V}$ |
| | Peak Wavelength | λ_p | --- | 940 | --- | nm | $I_F=20\text{mA}$ |
| | View Angle | $2\theta_{1/2}$ | --- | 30 | --- | Deg | $I_F=20\text{mA}$ |
| Output | Dark Current | I_{CEO} | --- | --- | 100 | nA | $V_{CE}=10\text{V}$ |
| | C-E Saturation Voltage | $V_{CE(sat)}$ | --- | --- | 0.4 | V | $I_C=2\text{mA}$ $E_e=1\text{mW/cm}^2$ |
| Transfer Characteristics | Collect Current | $I_C(ON)$ | 0.1 | --- | --- | mA | $V_{CE}=5\text{V}$ $I_F=20\text{mA}$ |
| | Rise time | t_r | --- | 20 | --- | μsec | $V_{CE}=2\text{V}$ $I_C=100\mu\text{A}$ |
| | Fall time | t_f | --- | 20 | --- | μsec | $R_L=1\text{K}\Omega$ |


EVERLIGHT

Typical Electrical/Optical/Characteristics Curves for IR







Typical Electro/Optical/Characteristics Curves for PT




Relative Collector Current vs Ambient Temperature




Collector Current vs. Irradiance




Collector Current vs. Ambient Temperature



Collector Current vs. Collector-emitter Voltage



Package Dimension



① :CATHODE ③ :COLLECTOR
② :ANODE ④ :EMITTER

- Notes:** 1.All dimensions are in millimeters
2.Tolerances unless dimensions ±0.25mm

Packing Quantity Specification

- 1000pcs/1Bag
- 1Bag/1Carton

Label Form Specification



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number
- X: Month
- Reference: Identify Label Number

DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.

EVERLIGHT